


digital™

LIVE FREE OR DIE


UNIX

Registered TM of UNIX System Laboratories,
A wholly owned subsidiary of Novell, Inc.

94B-0534



Unix History



What computers can run Unix?



Apple OS X Macs



Wireless internet routers




Google's Android phones



Airplane
entertainment
systems

The Terminal Window




the shell, the prompt, the command line


The Terminal Window

```
ubuntu@ip-10-4-230-31: ~/working - ssh - 141x44
ubuntu@ip-10-4-230-31:~/working$ ls -lc ~
total 444
drwxr-xr-x 13 ubuntu ubuntu 4096 2012-01-29 22:50 .
drwxr-xr-x  6 root    root   4096 2011-11-14 17:12 ..
-rw-r--r--  1 ubuntu ubuntu 3757 2012-03-12 12:11 .bash_history
-rw-r--r--  1 ubuntu ubuntu  220 2011-05-18 10:00 .bash_logout
-rw-r--r--  1 ubuntu ubuntu 3581 2011-11-14 14:10 .bashrc
lrwxrwxrwx  1 root    root    21 2011-11-14 12:25 bin -> ../../usr/proftpd/bin
drwxr-xr-x  2 ubuntu ubuntu 4096 2011-11-14 14:10 .byobu
drwxr-xr-x  4 ubuntu ubuntu 4096 2011-11-14 14:33 .cabal
drwxr-xr-x  5 ubuntu ubuntu 4096 2011-11-14 11:37 .cache
lrwxrwxrwx  1 root    root    20 2011-11-14 12:23 conf -> ../../usr/nginx/conf
-rwxrwxrwx  1 ubuntu ubuntu  997 2011-11-14 17:12 configure_freemx.sh
drwxr-xr-x  3 ubuntu ubuntu 4096 2012-01-28 22:52 .emacs.d
lrwxrwxrwx  1 root    root    21 2011-11-14 12:25 etc -> ../../usr/proftpd/etc
drwxr-xr-x  2 ubuntu ubuntu 4096 2011-11-14 12:51 .fontconfig
drwxr-xr-x  2 ubuntu ubuntu 4096 2011-11-14 14:18 .gconf
drwxr-xr-x  3 root    root   4096 2011-11-14 10:58 .gem
drwxr-xr-x  2 ubuntu ubuntu 4096 2011-11-14 14:51 .gnupg
lrwxrwxrwx  1 root    root    20 2011-11-14 12:23 html -> ../../usr/nginx/html
lrwxrwxrwx  1 root    root    25 2011-11-14 12:25 include -> ../../usr/proftpd/include
drwxr-xr-x  4 ubuntu ubuntu 4096 2011-11-28 17:49 .install
drwxr-xr-x  3 ubuntu ubuntu 4096 2011-11-14 12:27 .lein
-rw-r--r--  1 ubuntu ubuntu  65 2011-11-14 13:07 .leashes
lrwxrwxrwx  1 root    root    21 2011-11-14 12:25 lib -> ../../usr/proftpd/lib
lrwxrwxrwx  1 root    root    25 2011-11-14 12:25 libexec -> ../../usr/proftpd/libexec
lrwxrwxrwx  1 root    root    20 2011-11-14 12:23 logs -> ../../usr/nginx/logs
drwxr-xr-x  2 ubuntu ubuntu 4096 2011-11-14 12:51 .m2
drwxr-xr-x  2 ubuntu ubuntu 4096 2011-11-14 14:18 .matplotlib
-rw-r--r--  1 ubuntu ubuntu 2964 2012-01-29 22:50 .mysql_history
-rw-r--r--  1 ubuntu ubuntu  675 2011-11-14 14:10 .profile
drwxr-xr-x  2 root    root   4096 2011-11-14 12:25 .sbin
-rw-r--r--  1 ubuntu ubuntu  0 2011-11-14 11:37 .screenrc
lrwxrwxrwx  1 root    root    23 2011-11-14 12:25 share -> ../../usr/proftpd/share
drwxr-xr-x  2 ubuntu ubuntu 4096 2011-11-14 11:33 .ssh
-rw-r--r--  1 ubuntu ubuntu 338416 2012-01-29 10:12 .stacks-0.998.tar.gz
drwxr-xr-x  3 ubuntu ubuntu 4096 2011-11-14 13:44 .subversion
-rw-r--r--  1 ubuntu ubuntu  0 2011-11-14 11:38 .sudo_as_admin_successful
drwxr-xr-x  2 ubuntu ubuntu 4096 2012-01-29 04:42 .tmp
lrwxrwxrwx  1 root    root    21 2011-11-14 12:25 var -> ../../usr/proftpd/var
-rw-r--r--  1 ubuntu ubuntu 7522 2012-01-29 20:35 .viminfo
lrwxrwxrwx  1 ubuntu ubuntu  12 2012-01-28 22:49 .working -> /mnt/working
-rw-r--r--  1 ubuntu ubuntu 195 2011-12-12 12:04 .Xauthority
ubuntu@ip-10-4-230-31:~/working$
```

Make it comfortable to work in:


- Resize the window
- Change your font size
- Open multiple terminal windows






Obtain a cheat sheet


google “unix commands”



In UNIX everything is a file organized in a hierarchy



Paths



`/home/catchen/working`

Create a series of directories

```
ubuntu@ip-10-4-193-188:~$ mkdir shell
ubuntu@ip-10-4-193-188:~$ cd shell
ubuntu@ip-10-4-193-188:~/shell$ mkdir research
ubuntu@ip-10-4-193-188:~/shell$ ls
research
ubuntu@ip-10-4-193-188:~/shell$ cd research/
ubuntu@ip-10-4-193-188:~/shell/research$ mkdir seq
ubuntu@ip-10-4-193-188:~/shell/research$ ls
seq
ubuntu@ip-10-4-193-188:~/shell/research$ cd seq/
ubuntu@ip-10-4-193-188:~/shell/research/seq$ mkdir radtags
ubuntu@ip-10-4-193-188:~/shell/research/seq$ cd radtags/
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$ ls
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$ ls -la
total 8
drwxrwxr-x 2 ubuntu ubuntu 4096 2012-03-06 23:08 .
drwxrwxr-x 3 ubuntu ubuntu 4096 2012-03-06 23:08 ..
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$ pwd
/home/ubuntu/shell/research/seq/radtags
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$
```

% mkdir shell

% cd shell


% ls

Paths, cont

This shell view of the nested directories shell, research, seq, and radtags.....

```
ubuntu@ip-10-4-193-188:~$ mkdir shell
ubuntu@ip-10-4-193-188:~$ cd shell
ubuntu@ip-10-4-193-188:~/shell$ mkdir research
ubuntu@ip-10-4-193-188:~/shell$ ls
research
ubuntu@ip-10-4-193-188:~/shell$ cd research/
ubuntu@ip-10-4-193-188:~/shell/research$ mkdir seq
ubuntu@ip-10-4-193-188:~/shell/research$ ls
seq
ubuntu@ip-10-4-193-188:~/shell/research$ cd seq/
ubuntu@ip-10-4-193-188:~/shell/research/seq$ mkdir radtags
ubuntu@ip-10-4-193-188:~/shell/research/seq$ cd radtags/
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$ ls
total 8
drwxrwxr-x 2 ubuntu ubuntu 4096 2012-03-06 23:08 .
drwxrwxr-x 3 ubuntu ubuntu 4096 2012-03-06 23:08 ..
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$ pwd
/home/ubuntu/shell/research/seq/radtags
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$
```

....is equivalent to this GUI view of the same directories




Filename	Size	Modified
bin	21 B	11/14/11 4:25 AM
conf	20 B	11/14/11 4:23 AM
configure_freenx.sh	992 B	11/14/11 9:12 AM
etc	21 B	11/14/11 4:25 AM
html	20 B	11/14/11 4:23 AM
include	25 B	11/14/11 4:25 AM
install	4.0 KB	11/28/11 9:49 AM
lib	21 B	11/14/11 4:25 AM
libexec	25 B	11/14/11 4:25 AM
logs	20 B	11/14/11 4:23 AM
sbin	4.0 KB	11/14/11 4:25 AM
share	23 B	11/14/11 4:25 AM
shell	4.0 KB	3/6/12 3:08 PM
research	4.0 KB	3/6/12 3:08 PM
seq	4.0 KB	3/6/12 3:08 PM
radtags	4.0 KB	3/6/12 3:08 PM
stacks-0.998.tar.gz	330.4 KB	1/9/12 8:12 AM
tmp	4.0 KB	1/8/12 8:42 PM
var	21 B	11/14/11 4:25 AM
working	12 B	1/8/12 2:49 PM

And the radtags directory is uniquely identified by its path:
/home/ubuntu/shell/research/seq/radtags


Absolute and relative paths

How do I get to the Hotel Zlatý Anděl?




Absolute and relative paths


How do I get to the Hotel Zlatý Anděl?



Paths




Absolute Path




`/home/catchen/working`


Relative Path?




Special files -- '*dot*'




Special files -- ‘dot dot’



Relative Path



`../working`




Absolute Path:

`/home/catchen/working/foo`

Relative Path:

`../working/foo`




Absolute Path:

`/home/catchen/working/foo`

Absolute Path:

`/home/catchen/research/foo`



Relative Path: `../working/foo`

Relative Path: `./foo`

Absolute and relative paths

```
ubuntu@ip-10-4-193-188:~$ mkdir shell
ubuntu@ip-10-4-193-188:~$ cd shell
ubuntu@ip-10-4-193-188:~/shell$ mkdir research
ubuntu@ip-10-4-193-188:~/shell$ ls
research
ubuntu@ip-10-4-193-188:~/shell$ cd research/
ubuntu@ip-10-4-193-188:~/shell/research$ mkdir seq
ubuntu@ip-10-4-193-188:~/shell/research$ ls
seq
ubuntu@ip-10-4-193-188:~/shell/research$ cd seq/
ubuntu@ip-10-4-193-188:~/shell/research/seq$ mkdir radtags
ubuntu@ip-10-4-193-188:~/shell/research/seq$ cd radtags/
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$ ls
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$ ls -la
total 8
drwxrwxr-x 2 ubuntu ubuntu 4096 2012-03-06 23:08 .
drwxrwxr-x 3 ubuntu ubuntu 4096 2012-03-06 23:08 ..
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$ pwd
/home/ubuntu/shell/research/seq/radtags
ubuntu@ip-10-4-193-188:~/shell/research/seq/radtags$
```

Special Files

dot

dot dot

% ls .

% ls ..

% ls ../../

Binary programs - ls, cp, mkdir, etc.

```
ubuntu@ip-10-140-6-74:~$ ls /bin
```

bash	csch	getfacl	lsblk	ntfsck	readlink	true
bunzip2	dash	grep	lsmod	ntfscluster	rm	unlockmgr_server
busybox	date	gunzip	mkdir	ntfsnnp	rmadir	umount
bzcat	dbus-cleanup-sockets	gzexe	mknod	ntfsdecrypt	rmrno	uname
bzcomp	dbus-daemon	gzip	mktemp	ntfsdump_logfile	run-parts	uncompress
bzdiff	dbus-uuidgen	hostname	more	ntfsfix	rzsh	unicode_start
bzegrep	dd	init-checkconf	mount	ntfsinfo	sed	vdir
bzexe	df	initctl2dot	mountpoint	ntfsls	setfacl	which
bzfgrep	dir	ip	mt	ntfsmftalloc	setfont	ypdomainname
bzgrep	dmesg	kbd_mode	mt-gnu	ntfsmove	setupcon	zcat
bzip2	dnsdomainname	kill	mv	ntfstuncate	sh	zcmp
bzip2recover	domainname	ksh	nano	ntfswipe	sh.distrib	zdiff
bzless	dumpkeys	less	nc	open	sleep	zegrep
bzmore	echo	lessecho	nc.openbsd	openvt	static-sh	zfgrep
cat	ed	lessfile	netcat	pidof	stty	zforce
chacl	egrep	lesskey	netstat	ping	su	zgrep
chgrp	false	lesspipe	nisdomainname	ping6	sync	zless
chmod	fgconsole	ln	ntfs-3g	plymouth	tailf	zmore
chown	fgrep	loadkeys	ntfs-3g.probe	plymouth-upstart-bridge	tar	znew
chvt	findmnt	login	ntfs-3g.secaudit	ps	tcsh	zsh
cp	fuser	lowntfs-3g	ntfs-3g.usermap	pwd	tempfile	zsh4
cpio	fusermount	ls	ntfscat	rbash	touch	

ubuntu@ip-10-140-6-74:~\$

working research ...

% ls /bin

Relative and absolute paths

A shortcut to your 'home', tilde:

~

Moving through the filesystem:

cd

Knowing where you are:

pwd

% ls ~/

% cd ~/


% cd

% pwd

Relative and absolute paths

/home/tgac/shell/research/seq/radtags

```
tgac@Genotyping2: ~/shell/research/seq/radtags - ssh - 105x23
tgac@Genotyping2:~$ mkdir shell
tgac@Genotyping2:~$ cd shell
tgac@Genotyping2:~/shell$ mkdir research
tgac@Genotyping2:~/shell$ ls
research
tgac@Genotyping2:~/shell$ cd research/
tgac@Genotyping2:~/shell/research$ mkdir seq
tgac@Genotyping2:~/shell/research$ ls
seq
tgac@Genotyping2:~/shell/research$ cd seq/
tgac@Genotyping2:~/shell/research/seq$ ls
tgac@Genotyping2:~/shell/research/seq$ mkdir radtags
tgac@Genotyping2:~/shell/research/seq$ ls
radtags
tgac@Genotyping2:~/shell/research/seq$ ls -la
total 12
drwxrwxr-x 3 tgac tgac 4096 Nov  4 09:34 .
drwxrwxr-x 3 tgac tgac 4096 Nov  4 09:34 ..
drwxrwxr-x 2 tgac tgac 4096 Nov  4 09:34 radtags
tgac@Genotyping2:~/shell/research/seq$ cd radtags/
tgac@Genotyping2:~/shell/research/seq/radtags$ pwd
/home/tgac/shell/research/seq/radtags
tgac@Genotyping2:~/shell/research/seq/radtags$
```



% ls .

% ls ..

% ls ../../

% cd ~/

% cd shell/research

% pwd

Are you typing? You're doing it wrong.

Tab-completion:

- Tab once to complete uniquely
- Tab twice to see all possible completions

Up-arrow:

- Previous commands can be found by pressing “up-arrow”

‘history’

```
% cd /etc
```

```
% ls c <tab>
```

```
% pwd
```

```
% ls c <tab><tab>
```

```
bi610@ip-172-31-17-121: /etc — ssh — 92x40
bi610@ip-172-31-17-121:~/shell/research/seq/radtags$ cd /etc/
bi610@ip-172-31-17-121:/etc$ ls -l
total 868
-rw-r--r-- 1 root root 15070 Apr  4 04:30 a2ps.cfg
-rw-r--r-- 1 root root 2563 Apr  4 04:30 a2ps-site.cfg
drwxr-xr-x 3 root root 4096 Apr 16 18:26 acpi
-rw-r--r-- 1 root root 2981 Apr 16 18:25 adduser.conf
-rw-r--r-- 1 root root 10 Apr 16 18:27 adjtime
drwxr-xr-x 2 root root 4096 Jun 20 22:23 alternatives
drwxr-xr-x 8 root root 4096 Jun 20 21:30 apache2
drwxr-xr-x 3 root root 4096 Apr 16 18:25 apm
drwxr-xr-x 3 root root 4096 Apr 16 18:26 apparmor
drwxr-xr-x 8 root root 4096 Jun 19 22:10 apparmor.d
drwxr-xr-x 3 root root 4096 Jun 19 22:00 appport
drwxr-xr-x 6 root root 4096 Apr 16 18:27 apt
-rw-r----- 1 root daemon 144 Oct 21 2013 at.deny
-rw-r--r-- 1 root root 2177 Apr  9 01:03 bash.bashrc
-rw-r--r-- 1 root root 45 Mar 22 20:57 bash_completion
drwxr-xr-x 2 root root 4096 Jun 20 21:44 bash_completion.d
-rw-r--r-- 1 root root 356 Jan  1 2012 bindresvport.blacklist
-rw-r--r-- 1 root root 321 Apr 16 16:07 blkid.conf
lrwxrwxrwx 1 root root 15 Jun  3 20:54 blkid.tab -> /dev/.blkid.tab
drwxr-xr-x 2 root root 4096 Apr 16 18:26 byobu
drwxr-xr-x 3 root root 4096 Apr 16 18:25 ca-certificates
-rw-r--r-- 1 root root 7464 Apr 16 18:26 ca-certificates.conf
drwxr-xr-x 2 root root 4096 Apr 16 18:26 calendar
drwxr-s--- 2 root dip 4096 Apr 16 18:26 chatscripts
drwxr-xr-x 4 root root 4096 Apr 16 18:27 cloud
drwxr-xr-x 2 root root 4096 Apr 16 18:25 console-setup
drwxr-xr-x 2 root root 4096 Jun 19 22:10 cron.d
drwxr-xr-x 2 root root 4096 Jun 19 22:10 cron.daily
drwxr-xr-x 2 root root 4096 Apr 16 18:25 cron.hourly
drwxr-xr-x 2 root root 4096 Apr 16 18:25 cron.monthly
-rw-r--r-- 1 root root 722 Feb  9 2013 crontab
drwxr-xr-x 2 root root 4096 Jun 20 22:23 cron.weekly
-rw-r--r-- 1 root root 54 Apr 16 18:26 crypttab
drwxr-xr-x 4 root root 4096 Apr 16 18:26 dbus-1
-rw-r--r-- 1 root root 2969 Feb 23 14:30 debconf.conf
-rw-r--r-- 1 root root 11 Feb 20 02:43 debian_version
drwxr-xr-x 3 root root 4096 Jun 20 22:23 default
```

Three variants to ls

```
ls -l
```

provides a *long*
listing

```
ls -la
```

includes *all* files,
even hidden files

```
ls -lh
```

displays file sizes
in *human* readable
numbers

Four ways to view a text file

<code>more</code>	<code>head</code>	<code>tail</code>	<code>cat</code>
view a text file one screen full at a time	view the top 15 lines of a file	view the last 15 lines of a file	spit the whole file at once
space-bar: scroll q: quit	-n num controls the number of lines	-n num controls the number of lines	

Explore the file hierarchy

1. Move to the directory `/etc`

- What is the first line of the file `hosts` in the directory `/etc`?
- What is the relative file path to get to `/var/log` from here?
- What is the absolute path?

2. Move to the directory `/var/log/`

- What is the contents on line 73 of the `dpkg.log` file?
- Without changing directories, what is the second line of the `cpuinfo` file in the `proc` directory?
 - What is the command to read this file with a relative path?
 - An absolute path?

3. Move back to the root, what directories do you see?

4. Move back home, what are three ways to move home from the root?

Copy example files

Return to the directory in your home called 'shell'.

TSV file:

`~/unix/batch_1.genotypes_1.loc.gz`

FASTQ file:

`~/unix/s_1_sequence.txt.gz`

Tar Archive:

`~/unix/samples.tar.gz`

What is a tar archive?



tar = tape archive

Compress / Decompress

`gzip / gunzip`

`batch_l.genotypes_l.loc.gz`

`s_l_sequence.txt.gz`

Gzipped Tar archive

`tar xvfz`




`samples.tar.gz`

Tar archive



`tar xvf`

`samples.tar`


Sequencing on Illumina's Flow cell





Sequencing on Illumina's Flow cell, ctd.



Sequencing on Illumina's Flow cell, ctd.



Phred Quality Score



The FASTQ File Format

FASTA

```
>chromosome7
TTTGTCTGCAGGGGGACACGTCAAAGTCAAACGCAGGCAAGTTTGTGTTTATGTCCAGTGGATCTTTTGATTTT
ACATACTGCAGGGGTCAGGAGGATTATCTCCTCTGCAAGGTAACGCCTGCTGTAACCGTTGTTCTTCATCCTTTT
CCTAACTGCAGGGGCTGTCTTGTCAGGTCTGACAAGACATATGCAGGGGCTCAATTTGAGATAATTGCTCAATATA
```

FASTQ

```
@Sequence_137
TTTGTCTGCAGGGGGACACGTCAAAGTCAAACGCAGGCAAGTTTGTGTTTATGTCCAGTGGATCTTTTGATTTT
+Sequence_137
<?@DDDDDDHFHHFBB@GGIACFHGGHGBGHGCDHBEAHACHI=@CH.=7ACAHHADECDBCC66(6>@C>5@CACCA
```

```
@HWI-ST0747:162:C03AJACXX:3:1108:19763:106771 1:N:0:
TTTGTCTGCAGGGGGACACGTCAAAGTCAAACGCAGGCAAGTTTGTGTTTATGTCCAGTGGATCTTTTGATTTT
+
<?@DDDDDDHFHHFBB@GGIACFHGGHGBGHGCDHBEAHACHI=@CH.=7ACAHHADECDBCC66(6>@C>5@CACCA
```

ASCII Code

0	<NUL>	32	<SPC>	64	@	96	`	128	Ä	160	†	192	¿	224	‡
1	<SOH>	33	!	65	A	97	a	129	Å	161	°	193	¡	225	•
2	<STX>	34	"	66	B	98	b	130	Ç	162	¢	194	¬	226	‚
3	<ETX>	35	#	67	C	99	c	131	É	163	£	195	√	227	“
4	<EOT>	36	\$	68	D	100	d	132	Ñ	164	§	196	ƒ	228	‰
5	<ENQ>	37	%	69	E	101	e	133	Ö	165	•	197	≈	229	Â
6	<ACK>	38	&	70	F	102	f	134	Ü	166	¶	198	Δ	230	Ê
7	<BEL>	39	'	71	G	103	g	135	á	167	ß	199	«	231	Á
8	<BS>	40	(	72	H	104	h	136	à	168	®	200	»	232	Ë
9	<TAB>	41	)	73	I	105	i	137	â	169	©	201	…	233	È
10	<LF>	42	*	74	J	106	j	138	ä	170	™	202		234	Í
11	<VT>	43	+	75	K	107	k	139	å	171	’	203	À	235	Î
12	<FF>	44	,	76	L	108	l	140	ä	172	”	204	Ã	236	Ï
13	<CR>	45	-	77	M	109	m	141	ç	173	≠	205	Ö	237	Ì
14	<SO>	46	.	78	N	110	n	142	é	174	Æ	206	Œ	238	Ó
15	<SI>	47	/	79	O	111	o	143	è	175	Ø	207	œ	239	Ô
16	<DLE>	48	0	80	P	112	p	144	ê	176	∞	208	-	240	•
17	<DC1>	49	1	81	Q	113	q	145	ë	177	±	209	—	241	Ò
18	<DC2>	50	2	82	R	114	r	146	í	178	≤	210	“	242	Ú
19	<DC3>	51	3	83	S	115	s	147	ì	179	≥	211	”	243	Û
20	<DC4>	52	4	84	T	116	t	148	ï	180	¥	212	˘	244	Ü
21	<NAK>	53	5	85	U	117	u	149	î	181	μ	213	’	245	ı
22	<SYN>	54	6	86	V	118	v	150	ñ	182	θ	214	÷	246	˚
23	<ETB>	55	7	87	W	119	w	151	ó	183	Σ	215	◊	247	˛
24	<CAN>	56	8	88	X	120	x	152	ò	184	Π	216	ÿ	248	˜
25		57	9	89	Y	121	y	153	ô	185	π	217	ÿ	249	˘
26	<SUB>	58	:	90	Z	122	z	154	ö	186	ƒ	218	/	250	˙
27	<ESC>	59	;	91	[	123	{	155	õ	187	ª	219	€	251	˚
28	<FS>	60	<	92	\	124		156	ù	188	º	220	<	252	¸
29	<GS>	61	=	93	]	125	}	157	û	189	Ω	221	>	253	˝
30	<RS>	62	>	94	^	126	~	158	ü	190	æ	222	fi	254	˚
31	<US>	63	?	95	_	127		159	ü	191	ø	223	fi	255	˚

8 bits = 2^8 combinations = 256

0 1 1 1 1 0 0 1

$$0 \times 2^7 + 1 \times 2^6 + 1 \times 2^5 + 1 \times 2^4 + 1 \times 2^3 + 0 \times 2^2 + 0 \times 2^1 + 1 \times 2^0 = 121 = y$$

$$1 \times 10^2 + 2 \times 10^1 + 1 \times 10^0 = 121 = y$$

The FASTQ File Format, ctd

```
@HWI-ST0747:162:C03AJACXX:3:1108:19763:106771 1:N:0:
TTTGTCTGCAGGGGGACACGTCAAAGTCAAACGCAGGCAAGTTTGTGTTTATGTCCAGTGGATCTTTTGATTTT
+
<?@DDDDDDHFHHFBB@GGIACFHGGHGBGHGCDHBEAHACHI=@CH.=7ACAHHADECDBCC66(6>@C>5@CACCA
```

Quality Scores

```
SSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSS.....  
.....XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX..  
.....IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII..  
.....JJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJJ..  
LLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLLL..  
!"#$%&'()*+,-./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~  
|          |          |          |          |  
33         59        64         73         104        126
```

S - Sanger Phred+33, raw reads typically (0, 40)
X - Solexa Solexa+64, raw reads typically (-5, 40)
I - Illumina 1.3+ Phred+64, raw reads typically (0, 40)
J - Illumina 1.5+ Phred+64, raw reads typically (3, 40)
with 0=unused, 1=unused, 2=Read Segment Quality Control Indicator (bold)
(Note: See discussion above).
L - Illumina 1.8+ Phred+33, raw reads typically (0, 41)

ASCII values 33 - 73 = 0 - 40

‘F’ = 70

$$70 - 33 = 37$$

The FASTQ File Format, ctd

```
@HWI-ST0747:162:C03AJACXX:3:1108:19763:106771 1:N:0:  
TTTGTCTGCAGGGGGACACGTCAAAGTCAAACGCAGGCAAGTTTGTGTTTATGTCCAGTGGATCTTTTGATTTT  
+  
<?@DDDDDDHFHHFBB@GGIACFHGGHGBGHGCDHBEAHACHI=@CH.=7ACAHHADECDBCC66(6>@C>5@CACCA
```

$$70 - 33 = 37$$

Phred Quality Score	Probability of incorrect base call	Base call accuracy
10	1 in 10	90%
20	1 in 100	99%
30	1 in 1000	99.9%
40	1 in 10000	99.99%
50	1 in 100000	99.999%

Count raw reads:

```
wc -l s_1_sequence.txt
```

```
grep "@" s_1_sequence.txt  
grep -c "@" s_1_sequence.txt
```

```
grep -v "@" s_1_sequence.txt  
grep -v -c "@" s_1_sequence.txt
```

Count reads with barcode:

```
grep -c "^CGATA" s_1_sequence.txt
```


Special Files

STDIN, STDOUT, STDERR


The Shell's Killer App: **Pipes**



The Shell's Killer App: **Pipes**, ctd.



The Shell's Killer App: **Pipes**, ctd.



So what is the purpose of the
program **cat**?

cut

```
cut -f 10 batch_1.genotypes_1.loc
```

cut, capture the output

```
cut -f 1-10 batch_1.genotypes_1.loc > genos
```

cut, pipe the output to grep

```
cut -f 2 batch_1.genotypes_1.loc | grep -c "nnxnp"
```

```
cut -f 1-10,15,17 batch_1.genotypes_1.loc | grep "nnxnp" > genos2
```

Examine a marker, translating the output

```
cat batch_1.genotypes_1.loc | tr " " ", " | grep "^96053"
```

s_l_sequence.txt.gz

Decompress the file

1. Count the number of raw reads (250,000)
2. Count the number of reads with barcode CGATA (19,501)
3. Capture all FASTQ records for ACCAT into a file called sample_01.fq (you should get 18352 records, 73408 lines)
4. Determine the count of all barcodes in the file

```
286 CTAGT
7900 TCAGA
10659 ACTGC
10931 TGACC
11536 GAGAT
11871 CTGAA
14409 CGGCG
14508 TGGTT
18226 GAAGC
18352 ACCAT
18375 TCGAG
19501 CGATA
23012 AATTT
26336 GCATT
31136 CTAGG
```

1. Use **head** when building a command, **cat** once the command is working
2. Look at the **-n** option for the **head** command, the **-l** option for **wc**
3. The “^” character means “must occur at beginning of line” in a grep search
4. Look at the **grep** options: **-c**, **-v**, **-A**, **-B**
5. Read the man pages for **sort** and **uniq** to learn how to combine them

```
ls
gunzip
man
more
cat
wc
head
cut
grep
sort
uniq
>
|
```

Danger Is. #04 vs Middleton Is. #16 Fst

